

AUTOMATIC TAPING MACHINE **COM**® RA-200

STAND-ALONE TYPE USING ADHESIVE/SEMI ADHESIVE TAPE



■ FEATURES

- Using adhesive tapes, secure banding around slippery workpiece is resulted.
- Tapes available on the market can be used.
- Semi-adhesive tapes (masking tapes) will not damage the product surface.
Only negligible thin film of bonded remains there after removing banded tapes.
- 1 or 2 or 3 banding cycles in continuous run can be set.
- Operations can be started as soon as the power switch is turned on.
- Due to the through-hole design, even long bars can be banded.



■ PERFORMANCE

Banding size	Max. (width 200mm, height 160mm)
Banding speed	25 cycles (1 banding cycle)
Banding cycles	1 or 2 or 3 banding cycles

■ SPECIFICATIONS

Width	920mm
Height	1425mm (table height 912mm)
Depth	603mm
Weight	120kg
Power supply	230V, 50/60Hz, Three-Phase, 300W
Air pressure	0.5MPa
Air consumption	39dm ³ /min (ANR)

■ TAPE SPECIFICATIONS

Type of tape	Adhesive, Semi-adhesive
Tape width	12mm~50mm (outer diameter 250mm)

Special models can be designed and produced.
Design and specifications are subject to change without notice.

COM is Communication.

TAIYO SEIKI CO.,LTD.

4-3-7, Hino, Daitoh, Osaka, 574-0062, Japan.
Phone: 81-72-873-3739 Fax: 81-72-875-4324
URL: <http://www.com-machine.co.jp>
E-mail: taiyo@com-machine.co.jp